



DESCRIPTION

Grey Elastomeric Primer is a special blend of acrylic elastomeric resin, titanium dioxide, and fiber fillers. It is a heavy-bodied white coating that dries to an extremely tough but flexible waterproofing membrane layer. This general-purpose acrylic roof coating not only insulates and protects, but forms a rubberlike seal that moves and stretches with the normal expansion and contraction of the roof.

FEATURES

- Reduces heat loss
- Increases air conditioning efficiency
- Lowers roof temperature
- Makes roof last longer
- May be applied to wet or dry surfaces
- Covers approximately 80-100 sq. ft./gal at 6–8 mils thickness.

FIRST-AID

Eyes: Flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation. Get medical attention.

Skin: Remove contaminated clothing and clean skin with solvent solution and then wash with soap and water. Launder contaminated clothing before reuse. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and assist breathing as necessary. Get medical attention.

Ingestion: Get medical attention.

HMIS SYMBOL

Health	1
Fire	0
Reactivity	0
Personal Protection	

DIRECTIONS

Before applying Grey Elastomeric Primer to metal, felt, concrete, or composition roofing, sweep roof clean. For tar and gravel roofs, remove all loose gravel and tar clots and sweep clean, cleaning all crevices, removing all dust. On a damp surface or when used as an emergency repair, it is important to sweep standing water, ice, or snow away from problem area. Dry time between coats is 24 hours at 70°F.

CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions, and emergency procedures. **KEEP OUT OF REACH OF CHILDREN.**