

ROOF PATCH & REPAIR

Aerosol Roof Sealer

DESCRIPTION

Roof Patch and Repair is a portable, easy-to-use, thick black aerosol mastic coating that seals water leaks and fills cracks and voids on most roofing surfaces. Roof Patch and Repair provides an extremely durable sealer and coating that will not sag or drip in summer heat or crack or peel in winter cold. It sprays as a liquid, flows into low spots, cracks and crevices, then dries to a thick black rubberized coating.

Roof Patch and Repair can be used on asphalt and fiberglass shingles, built-up tar and gravel, single ply rubberized and granulated roofs, mobile home and RV roofs, flashings around chimneys, vents, and skylights. It helps seal concrete foundations and basements from water seepage and hydrostatic pressure leaks. Roof Patch and Repair provides an effective repair even when the surface is wet.

FEATURES

- Aerosol mastic sprays as liquid and dries to thick rubberized coating
- Can be used on wet surfaces
- Will not sag or drip in summer heat
- Will not crack or peel in winter cold
- Super thick formula
- No CFC's
- One can treats 2 to 12 square feet, depending on coating thickness
- 14 oz. aerosol

HOW TO USE

1. Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application.
2. Spray surface using a sweeping motion from a distance of 12 to 14 inches. For maximum effectiveness, apply several thin coats rather than one thick layer.
3. For best results, use only at can-temperature above 60° F. Spray a larger area than where leak has occurred and feather edges into surrounding area with lighter applications.
4. After each use, invert can and apply a short burst to clear actuator.

SPECIFICATIONS

Physical Form	Thick Liquid
Color	Black
Odor	Solvent
Specific Gravity	0.940
Flash Point (TOC)	60°F