



TRI-CHEM

EXTREME PATCH Heavy-Duty Floor Patch

DESCRIPTION

Extreme Patch was designed to patch, fill, renew, and mend pits, cracks, holes, crevasses, and joints in concrete, steel, or wood. Extreme Patch is ideal for anchoring machinery, leveling and building up concrete, steel or wood ramps, walks, docks, parking garages, driveways, and floors. Extreme Patch is ideal for use in warehouses, refineries, plants, mills, machine shops, aircraft hangers, food processing facilities, railroads, subways, train stations, mines and quarries, laboratories.

FEATURES

- Available in a variety of colors
- 24-hour cure time at room temperature
- Will cure under damp conditions
- Pot life of 90 minutes at 70° - 75°F in a 5oz. mass

AVAILABLE COLORS



DIRECTIONS

1. Ready floor by removing all loose materials.
2. Degrease floor with Extreme all-purpose degreaser for heavy incrustations of oil and grease. Optional: etch floor to provide roughness for better adhesions.
3. Pour two Parts A into one Part B and mix for approximately 1 1/2 - 2 minutes.
4. Add Part C slowly while continuing to stir until desired consistency is achieved.

FIRST-AID

Eyes: Flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation—get medical attention.

Skin: Flush with water and then wash with soap and water, launder contaminated clothing before reuse—get medical attention if irritation persists.

Inhalation: Remove to fresh air and assist breathing as necessary—get medical attention.

Ingestion: Immediately give a glass of water. If appreciable amounts have been swallowed get medical attention.

HMIS SYMBOL



CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions and emergency procedures.

KEEP OUT OF REACH OF CHILDREN.