

### DESCRIPTION

Roof Patch and Repair is a portable, easy-to-use, thick black aerosol mastic coating that seals water leaks and fills cracks and voids on most roofing surfaces. Roof Patch and Repair provides an extremely durable sealer and coating that will not sag or drip in summer heat or crack or peel in winter cold. It sprays as a liquid, flows into low spots, cracks and crevices, then dries to a thick black rubberized coating.

Roof Patch and Repair can be used on asphalt and fiberglass shingles, built-up tar and gravel, single ply rubberized and granulated roofs, mobile home and RV roofs, flashings around chimneys, vents, and skylights. It helps seal concrete foundations and basements from water seepage and hydrostatic pressure leaks. Roof Patch and Repair provides an effective repair even when the surface is wet.

### FIRST-AID

**Eyes:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek immediate medical attention.

**Skin:** Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use. Get medical attention immediately if symptoms occur.

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.

**Ingestion:** Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

### HMIS SYMBOL



Health	2
Fire	4
Reactivity	1
Personal Protection	

### CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions, and emergency procedures.  
**KEEP OUT OF REACH OF CHILDREN.**

### DIRECTIONS

1. Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application.
2. Spray surface using a sweeping motion from a distance of 12 to 14 inches. For maximum effectiveness, apply several thin coats rather than one thick layer.
3. For best results, use only at can-temperature above 60° F. Spray a larger area than where leak has occurred and feather edges into surrounding area with lighter applications.
4. After each use, invert can and apply a short burst to clear actuator.

### CONTENTS

Net Wt. 14 oz.