

## SEES PROOF

### Anti-Seize Lubricating Compound

#### DESCRIPTION

Sees Proof is an anti-seize lubricating compound for use as a sealing compound on high heat, high pressure gaskets, hoses, hydraulic fitting steel, brass, aluminum, or rubber. It is used on pre-combustion chamber fuel injection nozzles, valve cages; for boiler fittings, face pate studs and man hole covers, stay bolts, stay tubes, burner assemblies, pulleys, and sprockets. Sees Proof resists fresh and salt water on all engine and deck fittings and fasteners, etc. Sees Proof's temperature-resistant formulation protects against galling, seizing, pitting, fretting, corrosion, and distortion of threaded, keyed, splined, or press-fitted assemblies. It allows tighter, more vibration-proof seals using less torque while making disassembly easier.

#### DIRECTIONS

Pre-clean surface to be treated, removing an old contaminated grease, dirt, or grit. Brush on.

#### FIRST-AID

**Eyes:** Rinse eyes cautiously with lukewarm water while holding eyelids open for several minutes. Remove contact lenses if easy to do so. Continue rinsing for 15–20 minutes. Take care not to rinse contaminated water into unaffected eye or face. If irritation persists, get medical attention.

**Skin:** Remove contaminated clothing. Gently blot or brush away excess product. Wash with lukewarm water for 15–20 minutes. If feeling unwell, get medical attention.

**Inhalation:** Remove to fresh air and assist breathing as necessary—get medical attention if feeling unwell.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Get medical attention.

#### HMIS SYMBOL



Health	2
Fire	3
Reactivity	0
Personal Protection	

#### CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions, and emergency procedures. **KEEP OUT OF REACH OF CHILDREN.**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/ clothing/eye and face protection. Wash thoroughly after handling. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. In case of fire use water fog, dry chemical, or carbon dioxide to extinguish. Keep cool. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.