

THREE PATCH

100% Epoxy Concrete Patch

DESCRIPTION

Three Patch is an epoxy concrete patch of blended resin, hardener, and aggregate that is particularly useful where there is a chemical spillage on concrete floors, or where there is constant dampness or water spillage. Three Patch will waterproof the floor and protect against heavy trucking, barrel rolling, and other such abuses. Three Patch has excellent adhesion to clean surfaces and does not shrink on setting, being 100% solid materials.

Three Patch will end recurring floor repair problems, especially in plants where conventional floorings break down quickly due to intermittent chemical spillage, immersion or flow-off. A Three Patch surface can keep your plant floors sound, easy to clean, trouble-free, and sanitary

Three Patch is recommended for use in repair and resurfacing of concrete floors, resetting bricks, seal leaking cracks and joints in masonry, resurface stair treads, and to provide an "impervious skin" against acids, alkalis, petroleum products, salt water, and solvents. It will not wear or dust under high volume traffic

FEATURES

- One unit will cover 60 sq. ft. at 1/8" thick or 30 sq. ft. at 1/4" thick
- Pot life - 1/2 hours at 70° F
- Package size: 6-gallon kit

SPECIFICATIONS

Flexural Strength	2,500 psi
Compressive Strength	16,000 psi
Tensile Strength	1,800 psi
Impact Resistance	6 times greater than concrete
Abrasion Resistance	200 in lbs. for 1/4" layer on concrete
Adhesion	Consistently greater than concrete tensile strength
Weatherometer	No effect 1,000 hours