



# TRI-CHEM

## TRI-COVER I Roof Patch

### DESCRIPTION

Tri-Cover I is a special blend of refined fiber fillers; a heavy-bodied plastic roof cement of trowel consistency that dries to an extremely tough but flexible waterproofing membrane layer. Use for patching around roof flashings, stacks, skylights, gutters, chimneys, copings, etc., or to seal cracks and gaps in the roof surface.

### CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions, and emergency procedures. **KEEP OUT OF REACH OF CHILDREN.**

### HMIS SYMBOL

1	2
0	
Health	1
Fire	2
Reactivity	0
Personal Protection	

### DIRECTIONS

Before applying to metal, felt, concrete, or composite roofing, sweep roof clean. For tar and gravel roofs, remove all loose gravel and tar clots and sweep clean, cleaning all crevices and removing all dust. On a damp surface or when used as an emergency repair, it is important to sweep standing water, ice or snow away from the problem area.

Apply with a trowel or putty knife. On small hairline cracks, fill the crack and be sure to feather down all edges. Once the repair has been made, coat the entire surface with Tri-Cover II fiber roof coating. For ease of application in cold weather, keep material at room temperature before use.

### FIRST-AID

**Eyes:** Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to ophthalmologist.

**Skin:** Wash immediately with lots of water. Do not tear off solidified product from the skin. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Get medical attention.

**Inhalation:** Remove to fresh air—get medical attention if necessary.

**Ingestion:** Rinse mouth with water. Immediately after ingestion give lots of water to drink. Do NOT induce vomiting. Get medical attention if you feel unwell or if large quantities ingested.