

TRI-COVER I

Roof Patch

DESCRIPTION

Tri-Cover I is a special blend of refined fiber fillers; a heavy-bodied plastic roof cement of trowel consistency that dries to an extremely tough but flexible waterproofing membrane layer. Use for patching around roof flashings, stacks, skylights, gutters, chimneys, copings, etc., or to seal cracks and gaps in the roof surface.

FEATURES

- Made with refined asphalt, chemical binders, and fiber fillers
- Dries to form an extremely tough but flexible waterproof membrane
- Reduces heat loss
- Increases air conditioning efficiency
- Prolongs roof life
- Can be applied to wet or dry surfaces
- Easy to use
- Saves time and labor— no priming required
- Covers approximately 20 square feet per gallon spread 1/8 inch thick

HOW TO USE

Before applying to metal, felt, concrete, or composite roofing, sweep roof clean. For tar and gravel roofs, remove all loose gravel and tar clots and sweep clean, cleaning all crevices and removing all dust. On a damp surface or when used as an emergency repair, it is important to sweep standing water, ice or snow away from the problem area.

Apply with a trowel or putty knife. On small hairline cracks, fill the crack and be sure to feather down all edges. Once the repair has been made, coat the entire surface with Tri-Cover II fiber roof coating. For ease of application in cold weather, keep material at room temperature before use.

SPECIFICATIONS

Physical Form	Thick Paste
Color	Black
Odor	Solvent
Specific Gravity	1.07
Flash Point (TOC)	104°F

HMIS SYMBOL

Health	1
Flammability	1
Reactivity	0