

# WHITE ELASTOMERIC ROOF COATING

## Reflective Rubber Roof Coating

---

### DESCRIPTION

**White Elastomeric Roof Coating** is a thick, rubber-like coating that expands and contracts with the roof. The superior reflectivity lowers interior temperatures resulting in energy savings.

---

### FEATURES

- Resists cracking and peeling from severe heat and cold
- Excellent adhesion on metal, aged galvanized and pre-painted metal, urethane and polystyrene, polyester plastic panels, flat and barrel tiles, and some single-ply roofing materials
- Expands and contracts with the roof
- VOC-compliant with the Volatile Organic Compounds limits
- Easily applied with a soft brush, roller, or airless spray.
- Has excellent suspension and requires minimum stirring
- Custom colors available in minimum of 300 gallons
- Will cover 80 - 100 sq. ft. per gallon at 6 - 8 mils thickness.

---

### HOW TO USE

All surfaces to be coated must be power washed and thoroughly rinsed to allow the coating to adhere to the substrate. **DO NOT THIN.** For best results, apply with a soft brush, roller, or airless spray. Avoid excessive brushing. Apply at temperatures above 50°F. One coat will normally cover any previous coating, but two coats are recommended. If roof is hot, spray with water to prevent the coating from drying too fast. If coating is subjected to rain before it dries and some wash-off occurs, it is essential to wash stained surfaces as soon as possible with warm, soapy water. Dry time between coats is 24 hours at 70°F.

---

### SPECIFICATIONS

<b>Physical Form</b>	Thick Liquid
<b>Color</b>	White
<b>Odor</b>	Faint Ammonia Like
<b>Specific Gravity</b>	>1.0
<b>Flash Point (TCC)</b>	None